

Sub 036
~~A METHOD FOR GENERATING A DIVERSE SET OF TRAVEL OPTIONS~~

BACKGROUND

This invention relates to travel planning systems.

Computer travel planning systems such as airline
5 computer reservation systems used by airline reservation agents,
human travel agents, and automated travel agents such as internet
web sites , generally produce a relatively small set of
recommended travel options for a query that has a route and/or
time specification.

10 For air travel, usually the number of travel options
that a travel planning system produces is much smaller than the
total set that could possibly satisfy a traveller's request. For
example, a CRS may respond to a round-trip query specified by a
departure city and date and a return city and date with a set of
15 10 or so possible flight and fare combinations, even though there
may be thousands of combinations of flights that satisfy the
request.

20 In many cases, resource limitations prevent a travel
planning system from analyzing or generating more than a small
set of travel options. Moreover, for air travel it may be that
for each option the system needs to query airlines about seat
availability. The availability process places practical limits
the number of options that may be considered.

SUMMARY OF THE INVENTION

25 If a travel planning system is limited in the number of
options it can generate, it may be desirable that the travel
planning system consider or generate a diverse set of travel
options. The planning system can maximize its chance of
generating a good option by enforcing diversity in the set of
30 options generated.

The diversity process in the air travel planning system generates answers on several different airlines, thus the system is capable of satisfying a greater range of travellers.

Similarly, an air travel planning system that queries airlines about whether there are seats available on a limited number of flights may wish to choose flights at a diversity of flight times, in case flights at particular times of day are all full.

According to one aspect of the invention, travel planning system that outputs a set of travel options smaller than the complete set of travel options it has computed prunes the larger set of options to a smaller set with a diversity-based pruning process, where the larger set is represented by a compact representation.

One or more advantages are provided by the some of the aspects of the invention. The client process receives a set of pricing solutions provided in a compact representation. A preferred, compact representation of the set of pricing solutions is as a data structure comprising a plurality of nodes that can be logically manipulated using value functions to enumerate a set of pricing solutions. One preferred example is a graph data structure type particularly a directed acyclic graph that contains nodes that can be logically manipulated or combined to extract a plurality of pricing solutions. The client, can store and/or logically manipulate the set of pricing solutions to extract or display a subset of the set of pricing solutions without the need for additional intervention by the server.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing features and other aspects of the invention will be described in further detail by the accompanying drawings, in which:

FIG. 1 is a block diagram of a client server travel

planning system.

FIG. 2 is a flow chart showing a server process used in the system of FIG. 1.

FIG. 3 is a flow chart showing a client process used in the system of FIG. 1.

FIGS. 3A-3B are diagrammatic representations of pricing graphs.

FIGS. 4A-4B are flow charts showing a faring process used in the server process of FIG. 2.

FIG. 5 is a flow chart showing the process for constructing a pricing graph.

FIG. 6 is a block diagram showing the relationship between the pricing graph and a graphical user interface for the travel planning system of FIG. 1.

FIG. 7 is a flow chart showing various enumeration functions.

FIG. 8 is flow chart of a diversity process for selecting a diverse set of travel options.

FIG. 9 is a flow chart depicting an example of a diversity process.

FIG. 9A is a flow chart depicting a process used with a pricing graph.

FIG. 10 is a flow chart of a process to generate a prioritized list of travel requirements for the diversity process of FIG. 3.

FIG. 11 is a flow chart of template process used in the diverstiy process.

FIG. 12 is a flow chart of an alternative diverstiy process to generate a diverse set of travel options from a larger set of travel options.

DETAILED DESCRIPTION

Referring now to FIG. 1, a travel planning system 10 is shown. The travel planning system can be used with various forms of travel such as airline, bus and railroad and is particularly adapted for air travel. It includes a server computer 12 having a computer memory or storage media 14 storing a server process 15. The server process includes a scheduler process 16 and a faring process 18. The scheduler process 16 is any suitable scheduler process that will produce from a travel request sets of flights that can satisfy the request. The faring process 18 is a process that determines a set of valid fares and links the set of valid fares to the sets of flights to form a pricing solution. The server process 15 can be configured to produce other travel-related information as a result of a user query. For example, the server process 12 can produce routes or airline suggestions, optimal travel times and suggestions for alternative requests.

The travel planning system 10 also includes a plurality of databases 20a, 20b which store industry-standard information pertaining to travel (e.g., airline, bus, railroad, etc.). For example, database 20a can store the Airline Tariff Publishing Company database of published airline fares and their associated rules, routings and other provisions, the so-called ATPCO database. Database 20b can be an inventory of current availability of airline information for a particular carrier and so forth. The databases 20a-20b are typically stored locally and updated periodically by accessing remote resources 21a, 21b that maintain the respective databases.

~~The system 10 also includes a plurality of clients 30a-30c implemented by terminals or preferably personal computers. The clients 30a-30c are coupled to the server 12 via a network 22 which is also used to couple the remote resources (21a-21c) that supply the databases 20a-20b to the server 12. The network 22 can be any local or wide area network or an arrangement such as~~

A1
Cont'd

~~the Internet.~~

Sub
#2

~~The clients 30a-30e are preferably smart clients. That is, using client 30c as an illustrative example, client 30c includes a client computer system 32 including a computer memory or storage media 34 that stores a client process 36 and a set of pricing solutions 38. The set of pricing solutions 38 in one embodiment is provided from the server process 16 and comprises a set of fares that are valid for a journey, and associated information linking the fares to the flight segments of the journey.~~

10

The set of pricing solutions 38 is obtained from the server 12 in response to a user request sent from the client 30c to the server 12. The server 12 executes the server process 15 using the scheduling process 16 and the faring process 18 to produce a set of pricing solutions for a particular journey. If requested by the client, for example client 30c, the server 12 will deliver the set of pricing solutions 38 to the requesting client 30c. Under control of the client process 36, the requesting client 30c can store and/or logically manipulate the set of pricing solutions 38 to extract or display a subset of the set of pricing solutions as a display representation 41 on the monitor 40.

15

20

SERVER PROCESS

Referring now to FIG. 2, the server process 18 is preferably executed on the server computer 12 but could be executed on the client computer 32. The server process 18 is responsive to a user input query 48. The user input query 48 would typically include minimal information needed to determine a set of pricing solutions. This information typically requires at a minimum, an origin and a destination for travel. In addition, the information could also include times, dates and so forth.

25


30

This query 48 is fed to the scheduler process 16 that produces a large number of itineraries, that is, sequences of flight segments between the origin and destination for each slice of a journey. Examples of scheduler systems that may be used include the OAG Flight Desk (Official Airlines Guide, a division of Reed Travel Group) or schedule components of computer reservation systems (CRS=s) such as Sabre7, Apollo7, Amadeus7 and WorldSpan7. It is preferable in order to obtain the largest number of possible itineraries to use a scheduler with dynamic connection generation. Such a scheduler is described in co-pending patent application entitled SCHEDULER SYSTEM FOR TRAVEL PLANNING SYSTEM, Serial No. 09/109,622, filed on July 2, 1998 y Carl G. deMarcken et al. and assigned to the assignee of the invention and incorporated herein by reference.

The scheduler process 16 provides the itineraries to a faring process 18. The faring process 18 provides a set of pricing solutions 38 by finding valid fares corresponding to the itineraries produced by the scheduler process 16. The faring process 18 validates the fares for inclusion in the set of pricing solutions 38. A preferred faring process that places fares and itineraries in a compact data structrure referred to herein in as a pricing graph is described in co-pending patent application entitled TRAVEL PLANNING SYSTEM, Serial No. 09/109,327 , filed on July 2, 1998 by Carl G. deMarcken et al. and assigned to the assignee of the invention and incorporated herein by reference.

The set of pricing solutions 38 is used by an availability system 58 that interrogates an airline inventory database 20b to determine whether there are seats available on particular flights for particular pricing solutions. The availability system 58 uses the airline inventory database 20b as a filter to remove from the set of pricing solutions 38 those

pricing solutions for which there are not available seats. The availability system 58 is shown after the faring process 18. However, it could be included at nearly any point in the server process 18. In addition, it is shown being fed by the pricing solution when it may only receive flight information from the scheduler process 16 depending on the airline.

sub A3  ~~The client system 30c receives the results from the server process 18. These results are the set of pricing solutions 38 and/or pricing solutions based upon availability. The client process 36 executed in the client 30c uses this information or a subset of it to access a booking system 62 to provide a booking and reservation for a user selected, enumerated pricing solution, as will be described below.~~

CLIENT PROCESS

Referring now to FIG. 3, the client process 36 receives a listing of possible itineraries from the scheduler process 16 as well as the set of fares from the faring process 18 or the availability system 58. The set of pricing solutions 38, if obtained from the faring process 18, will include a large number of pricing solutions for which there is not any available inventory. Therefore, the components would need to be first checked out with an airline prior to booking. The set of pricing solutions 38 if obtained after the availability system 58 should contain pricing solutions which have a high degree of availability for booking on an airline.

In one embodiment, the set of pricing solutions 38 is provided in a compact representation 38'. A preferred, compact representation 38' of the set of pricing solutions 38 is as a data structure comprising a plurality of nodes including itineraries and fares and that can be logically manipulated using value functions to enumerate a set of pricing solutions. One

preferred example is a graph data structure type particularly a directed acyclic graph (DAG) that contains nodes that can be logically manipulated or combined to extract a plurality of pricing solutions.

5 ~~The client process 36 receives the flight information~~
from scheduler process 16 and the pricing solution from the
faring process 18 or the availability system 56 and enumerates
pricing solutions from the directed acyclic graph (DAG)
representation. The enumerated set of pricing solutions is
10 rendered in a graphical user interface 41 on the client monitor
~~40 (FIG. 1) in a manner as will be described below.~~

~~In response to user input 76, the client 40 can~~
manipulate travel options and can query the local copy of the DAG
to produce and display a subset of pricing solutions enumerated
from the DAG that satisfy the query 76. The manipulation process
used to control the display and change the travel options will be
~~described below.~~

~~A directed acyclic graph (DAG) is used to represent the~~
compact set of pricing solutions 38' since, in general, the
number of nodes needed to represent a typical pricing solution
will be substantially less than the actual number of pricing
solutions represented by the DAG. This significantly increases
the efficiency of transfer of a set of pricing solutions 38 from
the server process 18 to the client process 36. The DAG
20 representation also minimizes the storage requirements for the
set of pricing solutions 38. The DAG representation permits the
use of powerful search, sorting and manipulation processes to
produce various subsets of set of pricing solutions in an
efficient manner. As used herein, a directed acyclic graph (DAG)
30 is a set of nodes connected by directed arcs, that have no loops
of arcs in the same direction. If a node A is connected to a
~~node B via an arc A6B, then A is called a parent of B, and B is~~

A6
Cont'd

~~called a child of A. Each node may have zero, one or many
parents and zero, one or many children. As used herein, a
pricing solution that is represented by a graph will be referred
to as a pricing graph.~~

5 PRICING-GRAPH

A pricing graph that is produced by the faring process
18 and that represents a pricing solution includes three types of
nodes. The first type of node is an exclusive node, i.e., "OR"
node. An OR node N with children A, B and C represents an
10 exclusive choice between A, B and C. In other words, a pricing-
solution involving node N contains either the fares and
itineraries represented by A, or by B, or by C.

The second type of node is a collection node, i.e., an
"AND" node. An AND node N with children A, B and C represents
15 the sum of A, B and C. In other words, a pricing solution
involving N contains all the fares and itineraries found within
A, B and C.

The third type of node is a terminal node. Terminal
nodes are used to hold pricing objects. Pricing objects include
20 fares, itineraries, surcharges, routes, prices, booking codes,
taxes, rules/restrictions and other information of the user or
information that might be part of a travel option.
Collectively, "AND" and "OR" nodes are non-terminal nodes.

An example of the pricing-graph for a hypothetical
25 round-trip journey is presented below in TABLE 1. For each node,
its type and children are listed. If a node is a terminal, the
fare or itinerary is provided. Many nodes in the pricing graph
have more than one parent.

TABLE 1

Node	Type	Children	Object
0	OR	Nodes 1, 2, 3	
1	AND	Nodes 10, 14, 17, 17	

2	AND	Nodes 4, 5	
3	AND	Nodes 13, 15, 19, 19	
4	OR	Nodes 8, 9	
5	OR	Nodes 6, 7	
6	AND	Nodes 14, 16	
7	AND	Nodes 15, 18	
8	AND	Nodes 13, 16	
9	AND	Nodes 13, 18	
10	OR	Nodes 11, 12	
11	Itin.		Slice 1: BOS6LAX UA023
12	Itin.		Slice 1: BOS6DFW UA100, DFW6LAX UA103
13	Itin.		Slice 1: BOS6SAN NW222
14	Itin.		Slice 2: LAX6BOS UA515
15	Itin.		Slice 2: SAN6BOS NW223
16	Fare		UA BOS-LAX One-way AY
17	Fare		UA BOS-LAX Round-trip AQE7NR
18	Fare		NW BOS-SAN One-way AF
19	Fare		NW BOS-SAN Round-trip AH7NR

This pricing-graph represents a total of nine pricing solutions. These solutions can be extracted from the pricing-graph by descending from the root node, node 0. At every OR node a choice between children is made, and the choice determines the pricing-solution that results. At every AND node each child branch is descended, and the results are combined.

The term BOS6LAX UA023 is an itinerary which uses standard nomenclature to represent airports BOS and LAX, airline UA, and flight number 023. In general, conventional nomenclature used in the airline industry will be used herein.

~~The set of pricing-solutions that represented in the pricing-graph is presented in TABLE 2 below.~~

TABLE 2

Solution Number	Itineraries	Fares
1	Slice 1: BOS6LAX UA023 Slice 2: LAX6BOS UA515	UA BOS-LAX RT AQE7NR UA BOS-LAX RT AQE7NR
2	Slice 1: BOS6LAX UA023 Slice 2: LAX6BOS UA515	UA BOS-LAX OW AY UA BOS-LAX OW AY
3	Slice 1: BOS6LAX UA023 Slice 2: SAN6BOS NW223	UA BOS-LAX OW AY NW BOS-SAN OW AF

4	Slice 1: BOS6DFW UA100, DFW_LAX UA103 Slice 2: LAX6BOS UA515	UA BOS-LAX RT AQE7NR UA BOS-LAX RT AQE7NR
5	Slice 1: BOS6DFW UA100, DFW_LAX UA103 Slice 2: LAX6BOS UA515	UA BOS-LAX OW AY UA BOS-LAX OW AY
6	Slice 1: BOS6DFW UA100, DFW_LAX UA103 Slice 2: SAN6BOS NW223	UA BOS-LAX OW AY NW BOS-SAN OW AF
7	Slice 1: BOS6SAN NW222 Slice 2: LAX6BOS UA515	NW BOS-SAN OW AF UA BOS-LAX OW AY
8	Slice 1: BOS6SAN NW222 Slice 2: SAN6BOS NW223	NW BOS-SAN RT AH7NR NW BOS-SAN RT AH7NR
9	Slice 1: BOS6SAN NW222 Slice 2: SAN6BOS NW223	NW BOS-SAN OW AF NW BOS-SAN OW AF

The pricing-graph encodes the requirement that two itineraries are combined, one from slice 1 and one from slice 2, to form a pricing solution. Further, each itinerary is spanned by fares. In this case each pricing solution involves two fares, and round-trip fares are combined with like round-trip fares. In most circumstances, the number of nodes in the pricing-graph is small compared to the number of pricing-solutions those nodes represent. In many cases, a graph of 10,000 or so nodes can represent more than 1,000,000,000 pricing-solutions.

Referring now to FIG. 3A, the nodes of the pricing graph corresponding to Table 1 are shown, as an example. This figure illustrates the manner in which nodes in the pricing graph data structure as represented in Table 1 are combined to provide the pricing solutions shown in Table 2. Using pricing solution No. 1 (from TABLE 2) as an example, it can be shown that starting at the top of the graph at node 0, node 0 allows for a choice between nodes 1, 2, and 3. For pricing solution No. 1, Node 1 is chosen. Node 1 is the AND node that points to nodes 10 and 14, and has two pointers to node 17. Node 10 is an OR node which provides a choice of either nodes 11 or nodes 12. Node 11 as shown in FIG. 3A corresponds to a terminal node, the itinerary (>BOS-LAX UA 023). Node 12 corresponds to a terminal node, the itinerary BOS-DFN UA 100, DFN-LAX UA 103. This second choice in node 10 will provide pricing solutions corresponding to numbers

4-6, respectively. Therefore, selecting node 11 provides the itinerary for the first slice of solution 1. The fare for pricing solution 1 is provided by node 17 which has two pointers, one for each slice, to the fare "US BOS-LAX RT QE7NR"

5 corresponding to the fare shown for pricing solution no. 1 in Table 2 for the first slice. The second itinerary for pricing solution no. 1 is provided by node 14 which is referenced in AND node 1 that points to the itinerary LAX-BOS UA 515. The corresponding fare is also from terminal node 17 since it is a
10 round trip fare UA BOS-LAX RT QE7NR.

A second one of the pricing solutions, for example, the pricing solution 4 incorporating the terminal node 12 is provided by starting at node 0, and using node 1. Node 1 is an AND node requiring that nodes 17 (twice), node 10, and node 14 be
15 included. Node 10 is an OR node as mentioned above and is used to select node 12 which is the itinerary including segments ABOS6DFW UA 100" and ADFW6LAX UA 103". From node 1, node 14 the return itinerary LAX-BOS UA 515 also is reached. Node 17 also is chosen which contain the round trip fares. Similarly, the
20 remaining ones of the pricing solutions can be extracted from the pricing graph in the same manner as the two examples given above.

As mentioned above, a graph will typically have many more pricing solutions than nodes in the graph. The example just illustrated in conjunction with FIG. 3A has 9 pricing solutions
25 and 19 nodes which is an exception to that general rule. Another example of a pricing graph which does satisfy that general observation is shown in conjunction with FIG. 3B.

Referring now to FIG. 3B, a pricing graph is shown having 43 nodes N0-N42 that when combined represent 856 pricing
30 solutions. Each node in the pricing graph has a number associated with it corresponding to the number of pricing solutions that it represents. In order to make this illustration

of manageable size, identifiers (representing the nodes of the terminals) are substituted in the pricing graph for the actual terminal objects of the graph. Thus, as shown in FIG. 3B, outbound and return itineraries, and fare nodes are represented by the Nodes N20-N42.

This pricing graph (TABLE 3) has 9 itineraries which can be combined with 14 fares represented by 13 AND nodes and 7 OR nodes. The pricing objects are represented by 23 nodes. The pricing graph has a combined total of 43 nodes to represent 876 pricing solutions.

FIG. 3B shows examples of a pricing graph for a round trip LAX-BOS journey. This example shown in FIG. 3B is generally more representative of an outcome of a faring search. That is, generally the pricing graph represents more pricing solutions than nodes contained in the graph.

TABLE 3

Node	Type	Children	Object
0	AND	Nodes 1, 6, 11	
1	OR	Nodes 2, 3, 4	
2	AND	Nodes 5, 40	
3	AND	Nodes 41, 41	
4	AND	Nodes 42, 42	
5	OR	Nodes 39, 40	
6	OR	Nodes 7, 8, 9	
7	AND	Nodes 20, 10	
8	AND	Nodes 21, 10	
9	AND	Nodes 22, 10	
10	OR	Nodes 23, 24, 25, 26	
11	OR	Nodes 12, 13, 14, 16, 17, 18	
12	AND	Nodes 27, 15	
13	AND	Nodes 28, 15	
14	AND	Nodes 29, 15	
15	AND	Nodes 30, 31, 32	
16	AND	Nodes 33, 19	
17	AND	Nodes 34, 19	
18	AND	Nodes 35, 19	
19	OR	Nodes 36, 37, 38	
20	Itin.		Slice 1: LAX6DFW NW100, DFW6BOS AA223
21	Itin.		Slice 1: LAX6DFW NW137, DFW6BOS AA223
22	Itin.		Slice 1: LAX6DFW NW137, DFW6BOS AA414

23	Fare		DFW, LAX NW AY OW
24	Fare		DFW, LAX NW AF OW
25	Fare		DFW, LAX NW AC OW
26	Fare		DFW, LAX NW AQA7" OW
27	Itin.		Slice 2: BOS6DFW AA67, DFW6LAX CO716
28	Itin.		Slice 2: BOS6DFW AA67, DFW6LAX CO717
29	Itin.		Slice 2: BOS6DFW AA67, DFW6LAX CO719
30	Fare		DFW, LAX CO AF OW
31	Fare		DFW, LAX CO AC OW
32	Fare		DFW, LAX CO AY OW
33	Itin.		Slice 2: BOS6DFW AA852, DFW6LAX DL186
34	Itin.		Slice 2: BOS6DFW AA852, DFW6LAX DL180
35	Itin.		Slice 2: BOS6DFW AA852, DFW6LAX DL343
36	Fare		DFW, LAX DL AF OW
37	Fare		DFW, LAX DL AC OW
38	Fare		DFW, LAX DL AY OW
39	Fare		DFW, BOS AA AQE7NR RT
40	Fare		DFW, BOS AA AQE7IP RT
41	Fare		DFW, BOS AA AQE14NR RT
42	Fare		DFW, BOS AA AQE21NR RT

THE FARING SYSTEM

Referring now to FIGS. 4A and 4B, the faring process 18 includes a process 80 to retrieve itinerary sets for all slices in an itinerary. The itinerary sets are provided from the scheduler process 16 for each slice of a journey where a slice corresponds to a direction of travel. Thus, for example, for a round trip journey there would be two slices, one for the outbound part of the journey and one for the return part of the journey. The faring process 18 decomposes 82 the itinerary into faring atoms. As used herein, faring atoms refer to a sequence of flight segments or equivalently legs that are spanned by a single fare. For example, the itinerary

UA005 from DFW to BOS at 12:30 on 12NOV

UA010 from BOS to YYZ at 18:00 on 12NOV

AC121 from YYZ to YVR at 01:00 on 13NOV

permits the following faring-atoms as shown in TABLE 4.

TABLE 4

Faring-Atom Number	Legs and Departure Times
1	DFW6BOS UA005 12NOV 12:30
2	BOS6YYZ UA010 12NOV 18:00
3	DFW6BOS UA005 12NOV 12:30 BOS6YYZ UA010 12NOV 18:00
4	YYZ6YVR AC121 13NOV 01:00

A faring atom is represented by a data structure that preferably includes the following fields as shown in TABLE 5:

TABLE 5

Faring-Atom fields	Use
legs-and-departure-times	A list of legs and their departure times and dates.
faring-market	The faring-market that this faring-atom is in.
cached-results	A storage space used to eliminate redundant computation in the rule-checking process. As rule record-2s are applied to faring-atoms, the results are stored in this field. If the same record-2 is applied again, the answer is retrieved rather than recomputed.
priceable-unit-labels	A list of the priceable-unit-labels that the faring-atom enters into.

~~After the faring process 18 decomposes the itineraries into faring atoms, the faring process 18 retrieves fares 84 and rules 86 for each faring atom by accessing the fares/rules database 20a mentioned above. At this point a fare=s routing is retrieved from a routing database and applied to a faring atom. If the routing test fails, the fare cannot be applied to the faring atom and a fare component is not built.~~

~~The faring process 18 applies the rules 88 to the faring atoms to produce fare components. Fare-components are combinations of faring-atoms and fares. Fare-components (TABLE 6) are produced if a fare=s rules pass a preliminary check on a faring-atom. They are used to store deferred rules (e.g., deferred record-2s and combinability record-2s) that are applied at a later stage of processing. Fare components also store extra information produced during the rule-checking process, such as information about surcharges and penalties and discounts that are~~

A9 Cont'd
~~applied to the base fare price.~~

TABLE 6

Sub A31

Fare-Component fields	Use
fare	The fare-component=s fare.
faring-atom	The fare-component=s faring-atom.
deferred-record-2s	A list of non-category-10 record-2s that have not been fully evaluated.
combinability-record-2	If the fare=s rules include a category-10 (AFare Combinability record-2, it is stored here.
surcharges	A list of surcharges, penalties, discounts and other pieces of information produced during the rule-checking process.

10 ~~From the fare components the faring process 18 constructs 90~~
priceable units. For certain types of rules such as those which
require access to fares and/or flights from outside of the fare
component, those rules are stored in the fare component for later
or deferred evaluation. The priceable unit process 90, takes
valid fare components and constructs priceable units from the
fare components. This process 90 involves grouping fare
components from different slices and checking fare component
combination restrictions. At this stage of processing, the rules
~~deferred in step 88 are reapplied.~~

Sub A10

20 Priceable units are represented by priceable-unit-cores and
priceable-unit-labels. Priceable-unit-cores are collections of
fares and other information associated with fares within a
priceable-unit, such as discounts and penalties and surcharges.
Priceable-unit-cores (TABLE 7) are referenced by priceable-unit-
25 labels.

TABLE 7

30

Priceable-Unit-Core fields	Use
fares	A list of fares.
slice-numbers	A list of the slices the fares originate from.

surcharges	A list of surcharges, penalties, discounts and other pieces of information produced during the rule-checking process.
------------	---

Priceable-unit-labels group a set of priceable-unit-cores with sets of faring-atoms. Together, they are used to represent sets of priceable-units (TABLE 8).

TABLE 8

Priceable-Unit-Label fields	Use
priceable-unit-cores	A set of priceable-unit cores.
slice-numbers	A list of the slices the fares and faring-atoms originate from.
faring-atom-sets	A list of sets of faring-atoms, one per slice.

When all the fare components within a priceable unit are known, rules that were deferred from the processing 88 are applied 92 to the priceable unit sets of faring atoms.

~~After evaluation of the deferred record 2s at the priceable unit stage, the itineraries and priceable units are grouped together into complete set of pricing solutions. This occurs by a link process 94 that links itineraries to corresponding pricing units from different slices to provide the pricing solution. At this juncture, any remaining cross priceable unit fare combinability checks are performed to eliminate invalid combinations.~~

The linking process involves two additional data structures slice-label-sets and open-label-sets. Slice-label-sets group itinerary divisions by the multi-slice priceable-unit-labels they can enter into. In each slice of a journey, a unique slice-label-set is constructed for every set of multi-slice priceable-unit-labels. Each slice-label-set stores both the set of multi-slice priceable-unit-labels and a set of *itinerary-label-holders*, which contain single-slice priceable-unit-labels on a per-itinerary basis. Each slice-label-set is a pair of an itinerary

and a set of *division-label-holders*. Each of these division-label-holders is a pair of a division and a set of sets of single-slice priceable-unit-labels (TABLE 9).

TABLE 9

5	Slice-Label-Set fields		Use
	multi-slice-PU-labels		A set of multi-slice PU-labels.
	itinerary-label-holders		A set of itinerary-label-holders.
10	Itinerary-Label-Holder fields		Use
	itinerary		An itinerary.
	division-label-holders		A set of division-label-holders.
	Division-Label-Holder fields		Use
	division		An itinerary division.
	single-slice-PU-label-sets		A set of sets of single-slice PU-labels.

Open-label-sets (TABLE 10) are used to summarize the state of the linking process 94. Each is a set of "open" multi-slice priceable-unit-labels and a set of *backward-links*. Each of these backward-links is a pair of a slice-label-set and an open-label-set.

TABLE 10

20	Open-Label-Set fields		Use
	open-PU-labels		A set of open multi-slice PU-labels.
	backward-links		A set of backward-links.
25	Backward-Link fields		Use
	slice-label-set		A slice-label-set.
	open-label-set		An open-label-set.

~~The pricing solution resulting from the linking process 94 is used to construct a pricing graph from the various data structures built during the preceding processes. This pricing graph is transmitted to the client process or can be stored for later use or transmission. A pseudocode representation of the high level processing logic involved in the above search procedure is set out below in TABLE 11.~~

Sub
30
A12

TABLE 11

```

price-itinerary-sets(itinerary-sets, fare-database, rule-database, routing-database, environmental-information)
//
// itinerary-sets is a set of sets of itineraries, one per slice.
// environmental-information contains information about the passenger, the current date, the location
// where tickets will be purchased, and other non-itinerary-based information that is necessary for applying
// fare rules.
//
//
Let faring-market-sets = {}

// Construct itinerary-divisions, faring-markets and faring-atoms.
Let slice-number = 1
For itinerary-set in itinerary-sets
//
// create-divisions constructs the itinerary-divisions, faring-markets and faring-atoms for
// all the itineraries within a slice. It returns a set of faring-markets.
faring-market-sets += create-divisions(itinerary-set, slice-number, fare-database)
slice-number += 1

// Apply fare rules, constructing fare-components in each faring-market.
For faring-market-set in faring-market-sets
//
// apply-fare-rules constructs fare-components for each faring-market within a slice.
// This process contains pseudo-code for apply-fare-rules.
apply-fare-rules(faring-market-set, fare-database, rule-database,
routing-database, environmental-information)

// Create priceable-units.
// for create-priceable-units
create-priceable-units(faring-market-sets)

// Link itineraries between slices. This procedure returns either nil, if there are no pricing-solutions, or
// a Aroot open-label-set. This process is described in link-itineraries
Let root-object = link-itineraries(itinerary-sets)
If (root-object = nil)
return(nil)

// Create the pricing-graph from the data-structures that have been built in the preceding steps.
// This process includes psedo-code for create-pricing-graph.
Let root-node = create-pricing-graph(root-object)

// Return the pricing graph.
return(root-node)

```

PRICING GRAPH

⁵ ~~Referring now to FIG. 5, a pricing graph 38' (FIG. 3) is produced containing logically combinable nodes that can be used~~

SUB
A13

to efficiently and compactly represent a set of pricing solutions 38 (FIG. 1). The pricing graph 38' as used herein is a so-called directed acyclic graph although other types of representations could be used. For example, a grammar could be used.

The pricing graph 38' is constructed 300 from data structures 302 (summarized below in TABLE 12 and mentioned in conjunction with FIGS. 4A-4B) provided during the preceding processes. The data structures convert 304 to one or more nodes in the pricing graph. The open-label-set data structure becomes an OR node and its children are the converted versions of its backward links. Each backward link in the open label set is converted to an AND node. If a pricing object is shared, for example, a priceable unit core is shared between several priceable unit labels, then its counterpart nodes in the pricing graph will be shared so that the size of the pricing graph is not unnecessarily enlarged. The converted nodes are placed 306 in the pricing graph nodes. Terminal objects such as fares and itineraries undergo essentially no conversion. They are placed 308 into special terminal nodes with no children and are obtained from the various data structures that have the pricing objects.

TABLE 12

Data-Structure Type	Type	Child Fields
open-label-set	OR	<i>backward-links</i> (each a backward-link).
backward-link	AND	<i>open-label-set</i> (an open-label-set). <i>slice-label-set</i> (a slice-label-set).
slice-label-set	AND (OR)	<i>multi-slice-PU-labels</i> (each a priceable-unit-label). <i>itinerary-label-holders</i> (each an itinerary-label-holder). The itinerary-label-holders are put into an OR and the OR is placed under the AND, which also includes all multi-slice-PU-labels.
itinerary-label-holder	AND (OR)	<i>itinerary</i> (an itinerary). <i>division-label-holders</i> (each a division-label-holder). The division-label-holders are put into an OR and the OR is placed in an AND with the itinerary.

division-label-holder	OR (AND)	<i>single-slice-PU-label-sets</i> (each a set of sets of PU-labels). The inner sets are put into ANDs, and these are all embedded under an OR.
priceable-unit-label	OR	<i>priceable-unit-cores</i> (each a priceable-unit-core).
priceable-unit-core	AND	<i>fares</i> (each a fare). <i>surcharges</i> (each a surcharge, penalty, discount, etc.)
fares	Term	
itinerary	Term	
surcharge	Term	

In cases where a node has only one child, there is no need to produce the node. Rather, a direct link can be passed to its child. This does not alter the interpretation of the pricing-graph, but can result in a smaller graph.

The pseudo-code below TABLE 13 summarizes construction of the pricing graph, given the "root" open-label-set that is the output of the linking process.

TABLE 13

create-pricing-graph(root-object)

Let nodes = {}

Subroutine convert-object(object)

// Convert the object and cache the result, so that nodes with multiple parents are shared

Let node = find(object, nodes)

If (node = nil)

node = convert(object)

nodes += node

return(node)

Subroutine convert-objects (objects)

// Convert the set of objects and return a set of nodes.

Let result = {}

For object in objects

result += convert-object(object)

return(result)

Subroutine create-node(children, type)

// Create a node of type type with children children, if there is more than one child.

// Otherwise the node is unnecessary, and the only child is returned.

If (length(children) = 1)

return(first(child))

Else

Let node = new-node()

node.type = type

node.children = children

node.terminal-object = nil

return(node)

```

Subroutine convert(object)
  Let object-type = type(object)

  If (type = open-label-set)
    return(create-node(convert-objects(object.backward-links), OR))
  Else If (type = backward-link)
    return(create-node(list(convert-object(object.slice-label-set), convert-object(object.open-label-set)), AND))
  Else If (type = slice-label-set)
    Let children = convert-objects(object.multi-slice-PU-labels)
    children += create-node(convert-objects(object.itinerary-label-holders), OR)
    return(create-node(children, AND))
  Else If (type = itinerary-label-holder)
    Let children = convert-objects(object.division-label-holders)
    children += create-node(convert-objects(object.itinerary), OR)
    return(create-node(children, AND))
  Else If (type = division-label-holder)
    Let children = {}
    For single-slice-PU-label-set in object.single-slice-PU-label-sets
      children += create-node(convert-objects(single-slice-PU-label-set), AND)
    return(create-node(children, OR))
  Else If (type = priceable-unit-label)
    return(create-node(convert-objects(object.priceable-unit-cores), OR))
  Else If (type = priceable-unit-core)
    return(create-node(append(convert-objects(object.fares), convert-objects(object.surcharges)), AND))
  Else // object is a terminal.
    Let node = new-node()
    node.type = terminal
    node.children = {}
    node.terminal-object = object
    return(node)

return(convert-object(root-object))

```

TABLE 13 (cont.)

~~The pricing graph 38' resulting from the search procedure 54~~
 provides a compact way for representing a very large number of
 set of pricing solutions. By the above process, it is often
 possible to obtain a very large number of pricing solution
 components. Although the number of pricing solutions can be
 returned in the form of a simple list, this is not desirable. A
 very large number of pricing solutions can be difficult to
 manipulate, enumerate and interrogate and to transfer/transmit
 across a network since the amount of data involved is very large.
 The pricing graph 38' provides a more compact way of representing
 these pricing solutions. ~~The compact representation of the~~

range of set of pricing solutions is generated where choices are represented explicitly and redundancy is removed wherever possible.

5 *Sub A38*
~~As mentioned above, the pricing graph 38' produced by the search procedure 54 includes three types of nodes. The first type of node is a node that represents choices called "LOGICAL OR" nodes. The second type of node is a node that represents collections referred to as "LOGICAL AND" nodes. A third type of node represented in the pricing graph is a terminal node that~~
10 ~~represents pricing objects.~~

15 A data structure representation (TABLE 14) of the nodes is set out below. Each node contains a "type", which specifies whether the node is an AND node, an OR node or a terminal node. The data structure also contains either list of children (if the node is an AND node or an OR node) or a terminal object (if the node is a terminal). The node contains fields that store values used by algorithms that manipulate the pricing graph 38'.

TABLE 14

20 *Sub A38*

Node fields	Use
type	Either AND, OR or TERMINAL
children	A list of child-nodes, if node is AND or OR.
terminal-object	A terminal-object such as a fare or itinerary, if the node is TERMINAL.
active?	True or false, depending on whether the node is active.
inner-value	The node=s minimum possible inner-value.
outer-value	The node=s minimum possible outer-value.
total-value	The node=s minimum possible total-value.
best-child	For OR-nodes, the child with the least-positive inner-value.

25

30 As mentioned above, the pricing graph 38' is a compact representation of a set of set of pricing solutions. The typical number of set of pricing solutions represented by pricing graph ranges from tens of millions into hundreds of billions with the

number of nodes in the graph ranging from thousands to tens of thousands. The pricing graph can be easily stored and/or transmitted over a network or other connection to a client and represents complete representation of all or substantially all of possible pricing solutions. Therefore, the pricing graph 38' can be used by a smart client without further intervention from the server 12.

MANIPULATING THE PRICING-GRAPH

~~Referring now to FIG. 6, a high-level illustration of a~~
process 300 that operates on the pricing graph 38' typically as a client process 36 on the client computer system is shown. The process 300 includes a user query 302 that passes parameters into a process 304 and a value function 306 to extract from the pricing graph 38' certain pricing solutions 308 that satisfy parameters specified by the user query 302. The extracted pricing solutions are returned as a list 308 or other representation. Generally the pricing solutions are displayed on the display 40. Display software 309 handles production of GUI=41 to present the information.

~~The pricing solution list 308 will contain pricing solutions~~
extracted from the pricing graph 38' in accordance with user specified parameters from the user query 302 using one of the processes 304 and one of 7, illustrative processes are shown. In particular, in response to the user query 302, one of the processes is executed. The processes 304 can comprise a find best "value" and pricing solutions associated with the value (e.g., price) process 304a; find best "value" and pricing solutions associated with the value for "node" (e.g., find best price for a particular itinerary) process 304b; an enumeration for "N" pricing solutions 304c; or an enumeration process that lists the pricing solutions according to some "value."

Additional enumeration processes can be provided to produce query results corresponding to different ways of looking at pricing solutions extracted from the pricing graph 38'. A node invalidating process 304e that invalidates selected nodes from contributing to a pricing solution is also included.

Examples of each of these processes are set forth below.

Efficient algorithms 304 are used for manipulating this representation to extract information of interest and to enumerate set of pricing solutions from the structure. For example, it is possible to quickly extract the cheapest solution; to find the cheapest solution involving selected fares and itineraries; to verify whether any pricing solution remains if specific fares or itineraries are excluded; to enumerate solutions under various orderings and so forth. Furthermore, the representation is compact enough so that it can be efficiently stored and transmitted such as from the server to the client. One benefit, therefore, is that after a single fare search 54 in the server process 16, the server process 16 transfers the pricing graph 38 to the client process 36. The client process 36 can examine and manipulate the large space of pricing solutions represented in the pricing graph 38' without further interaction with the server process 18.

For the set of pricing solutions represented by the pricing graph 38' to be useful, processes are provided to extract pricing solutions from the graph and manipulate the set of pricing solutions, as depicted in FIG. 7. In general, each of the enumeration processes to be described operate on the pricing graph to extract pricing solutions from the pricing graph according to particular criteria that can be set, for example, by a client system 30c (FIG. 2) in response to a user query 48 (FIG. 4). Examples of user queries as well as a display representation for information extracted from the pricing graph will be

A20
Cont'd

~~described below.~~

5 An example of an enumeration function enumerates pricing solutions in a specific order. For example, an enumeration function can enumerate the 100 cheapest pricing solutions represented by the pricing graph 38'. A second enumeration function can find extreme points of the set of pricing solutions. This can be used, for example, to find the most convenient pricing solution. In addition, a value function can specify a minimum value of some value over the set of pricing solutions

10 that involve a particular node. One value function finds for each itinerary the cheapest pricing solution that involves that itinerary or the shortest total duration of any pricing solution that involves that itinerary.

15 In addition, each of the above operations can be performed on a subset of the graph. For example, it may be desirable to enumerate the 100 cheapest solutions that involve a given itinerary or finding the most convenient solution that involves only refundable fares or includes only certain airlines or excludes certain airlines.

20 **VALUE FUNCTIONS**

~~There are many processes or operations on the pricing graph 38' use a value-function, a function that operates on the terminal nodes of the pricing graph 38' and returns a numerical value that can be used to rank pricing-solutions. Examples of value-functions include price computed by summing the prices of fares (and penalties and surcharges) in a pricing-solution, duration, or convenience (that might be a mix of total travel-time with penalties for stops and airline-changes, for example), or mixes of each.~~

30 Many of the processes used to manipulate the pricing graph 38' depend on a value-function being decomposable into the sum of

a second function that is applied to individual terminal nodes in the pricing-graph. The "price value function" meets this requirement, because the total price of a pricing-solution is equal to the sum of the prices of fares. Many expressions of convenience also meet this requirement, including those that can be computed as the sum of a function applied to individual itineraries. However, there are some value-functions that cannot be placed into this form. An example is a "convenience" function that checks whether travel in different slices is on the same airline. Such a function depends on all itineraries at once.

In general, in the discussion below, the term node-value-function is used to refer to a function that is applied to individual nodes in the pricing-graph, and summed to produce the value of an entire itinerary. The term value-function is used for the more general case of a function that may or may not be decomposable into the sum of a node-value-function applied to each terminal in the pricing-graph.

FINDING THE BEST PRICING SOLUTION

The first process 304a is an example of one that finds extreme points of the set of pricing-solutions, such as the cheapest pricing-solution.

Assuming that it is desired to find a pricing-solution that minimizes some value-function that can be decomposed into a node-value-function F , the best pricing solution could be found by enumerating all pricing-solutions and applying F to each of them. This is impractical because of the large number of set of pricing solutions.

The Best Price algorithm 304a efficiently finds the cheapest (best) price by starting at the "bottom" of the pricing-graph and constructing the best solution for each node by looking at the best solution of its children. In this way it works in one

pass from the bottom of the graph to the top. At the end of the process the root node contains the best pricing solution for the entire pricing graph 38.

The algorithm proceeds as follows: first, the nodes in the graph are ordered by depth and placed in a list, so that iterating over the list ensures that a child node is always encountered before its parent(s). Then, iterating across the list, the best value of F is computed for each node, using the already-computed values of F for its children. At this point every node in the graph is marked with its inner-value. The inner-value of a node is the best possible value of the function F on the set of (partial) pricing-solutions represented by the node. As inner-values are computed, for every OR node the child with the lowest inner-value is computed and stored. Finally, the best pricing solution can be constructed by starting at the root of the graph and collecting children. Whenever an OR node is encountered, the best child is chosen (the child with the lowest inner-value).

If a node is a terminal fare or itinerary, then its inner-value is the value of F applied to the node. If the node is an AND, representing a combination, then the minimum value of F over the partial solutions it represents is the sum of the minimum values of F over the partial solutions represented by each of its children. If a node is an OR, representing a choice, then the minimum value of F over the partial solutions it represents is found by making the optimal choice of children, that is, the child with the minimum inner-value. So the inner-value of an OR is the minimum of the inner-values of its children.

The pseudo-code in TABLE 15 summarizes the computation of inner-values. The function sort-nodes takes a root node and returns a list of all nodes under it, sorted by depth with the root node at the end. The procedure compute-inner-values takes

in a sorted list of nodes as would be produced by sort-nodes, and
a node-value-function. The procedure find-optimal-solution takes
in a root-node and a node-value-function, calls sort-nodes and
compute-inner-values to calculate inner-values for all nodes in
5 the pricing-graph, and constructs a pricing-solution.

4100 4101 4102 4103 4104 4105 4106 4107 4108 4109 4110 4111 4112 4113 4114 4115 4116 4117 4118 4119 4120 4121 4122 4123 4124 4125 4126 4127 4128 4129 4130 4131 4132 4133 4134 4135 4136 4137 4138 4139 4140 4141 4142 4143 4144 4145 4146 4147 4148 4149 4150 4151 4152 4153 4154 4155 4156 4157 4158 4159 4160 4161 4162 4163 4164 4165 4166 4167 4168 4169 4170 4171 4172 4173 4174 4175 4176 4177 4178 4179 4180 4181 4182 4183 4184 4185 4186 4187 4188 4189 4190 4191 4192 4193 4194 4195 4196 4197 4198 4199 4200 4201 4202 4203 4204 4205 4206 4207 4208 4209 4210 4211 4212 4213 4214 4215 4216 4217 4218 4219 4220 4221 4222 4223 4224 4225 4226 4227 4228 4229 4230 4231 4232 4233 4234 4235 4236 4237 4238 4239 4240 4241 4242 4243 4244 4245 4246 4247 4248 4249 4250 4251 4252 4253 4254 4255 4256 4257 4258 4259 4260 4261 4262 4263 4264 4265 4266 4267 4268 4269 4270 4271 4272 4273 4274 4275 4276 4277 4278 4279 4280 4281 4282 4283 4284 4285 4286 4287 4288 4289 4290 4291 4292 4293 4294 4295 4296 4297 4298 4299 4300 4301 4302 4303 4304 4305 4306 4307 4308 4309 4310 4311 4312 4313 4314 4315 4316 4317 4318 4319 4320 4321 4322 4323 4324 4325 4326 4327 4328 4329 4330 4331 4332 4333 4334 4335 4336 4337 4338 4339 4340 4341 4342 4343 4344 4345 4346 4347 4348 4349 4350 4351 4352 4353 4354 4355 4356 4357 4358 4359 4360 4361 4362 4363 4364 4365 4366 4367 4368 4369 4370 4371 4372 4373 4374 4375 4376 4377 4378 4379 4380 4381 4382 4383 4384 4385 4386 4387 4388 4389 4390 4391 4392 4393 4394 4395 4396 4397 4398 4399 4400 4401 4402 4403 4404 4405 4406 4407 4408 4409 4410 4411 4412 4413 4414 4415 4416 4417 4418 4419 4420 4421 4422 4423 4424 4425 4426 4427 4428 4429 4430 4431 4432 4433 4434 4435 4436 4437 4438 4439 4440 4441 4442 4443 4444 4445 4446 4447 4448 4449 4450 4451 4452 4453 4454 4455 4456 4457 4458 4459 4460 4461 4462 4463 4464 4465 4466 4467 4468 4469 4470 4471 4472 4473 4474 4475 4476 4477 4478 4479 4480 4481 4482 4483 4484 4485 4486 4487 4488 4489 4490 4491 4492 4493 4494 4495 4496 4497 4498 4499 4500 4501 4502 4503 4504 4505 4506 4507 4508 4509 4510 4511 4512 4513 4514 4515 4516 4517 4518 4519 4520 4521 4522 4523 4524 4525 4526 4527 4528 4529 4530 4531 4532 4533 4534 4535 4536 4537 4538 4539 4540 4541 4542 4543 4544 4545 4546 4547 4548 4549 4550 4551 4552 4553 4554 4555 4556 4557 4558 4559 4560 4561 4562 4563 4564 4565 4566 4567 4568 4569 4570 4571 4572 4573 4574 4575 4576 4577 4578 4579 4580 4581 4582 4583 4584 4585 4586 4587 4588 4589 4590 4591 4592 4593 4594 4595 4596 4597 4598 4599 4600 4601 4602 4603 4604 4605 4606 4607 4608 4609 4610 4611 4612 4613 4614 4615 4616 4617 4618 4619 4620 4621 4622 4623 4624 4625 4626 4627 4628 4629 4630 4631 4632 4633 4634 4635 4636 4637 4638 4639 4640 4641 4642 4643 4644 4645 4646 4647 4648 4649 4650 4651 4652 4653 4654 4655 4656 4657 4658 4659 4660 4661 4662 4663 4664 4665 4666 4667 4668 4669 4670 4671 4672 4673 4674 4675 4676 4677 4678 4679 4680 4681 4682 4683 4684 4685 4686 4687 4688 4689 4690 4691 4692 4693 4694 4695 4696 4697 4698 4699 4700 4701 4702 4703 4704 4705 4706 4707 4708 4709 4710 4711 4712 4713 4714 4715 4716 4717 4718 4719 4720 4721 4722 4723 4724 4725 4726 4727 4728 4729 4730 4731 4732 4733 4734 4735 4736 4737 4738 4739 4740 4741 4742 4743 4744 4745 4746 4747 4748 4749 4750 4751 4752 4753 4754 4755 4756 4757 4758 4759 4760 4761 4762 4763 4764 4765 4766 4767 4768 4769 4770 4771 4772 4773 4774 4775 4776 4777 4778 4779 4780 4781 4782 4783 4784 4785 4786 4787 4788 4789 4790 4791 4792 4793 4794 4795 4796 4797 4798 4799 4800 4801 4802 4803 4804 4805 4806 4807 4808 4809 4810 4811 4812 4813 4814 4815 4816 4817 4818 4819 4820 4821 4822 4823 4824 4825 4826 4827 4828 4829 4830 4831 4832 4833 4834 4835 4836 4837 4838 4839 4840 4841 4842 4843 4844 4845 4846 4847 4848 4849 4850 4851 4852 4853 4854 4855 4856 4857 4858 4859 4860 4861 4862 4863 4864 4865 4866 4867 4868 4869 4870 4871 4872 4873 4874 4875 4876 4877 4878 4879 4880 4881 4882 4883 4884 4885 4886 4887 4888 4889 4890 4891 4892 4893 4894 4895 4896 4897 4898 4899 4900 4901 4902 4903 4904 4905 4906 4907 4908 4909 4910 4911 4912 4913 4914 4915 4916 4917 4918 4919 4920 4921 4922 4923 4924 4925 4926 4927 4928 4929 4930 4931 4932 4933 4934 4935 4936 4937 4938 4939 4940 4941 4942 4943 4944 4945 4946 4947 4948 4949 4950 4951 4952 4953 4954 4955 4956 4957 4958 4959 4960 4961 4962 4963 4964 4965 4966 4967 4968 4969 4970 4971 4972 4973 4974 4975 4976 4977 4978 4979 4980 4981 4982 4983 4984 4985 4986 4987 4988 4989 4990 4991 4992 4993 4994 4995 4996 4997 4998 4999 5000

TABLE 15

```

sort-nodes(node)

  Let nodes = {}
  For child in node.children
    nodes = append(nodes, sort-nodes(child))
  nodes += node
  return(nodes)

compute-inner-values(sorted-nodes, node-value-function)

For node in sorted-nodes
  If (node.type = terminal)
    node.inner-value = apply(node-value-function, node.terminal-object)
  Else If (node.type = OR)
    node.inner-value = infinity
    For child in node.children
      If (child.inner-value < node.inner-value)
        node.inner-value = child.inner-value
        node.best-child = child
  Else If (node.type = AND)
    node.inner-value = 0
    For child in node.children
      node.inner-value += child.inner-value

find-optimal-solution(root-node, node-value-function)

Subroutine get-node-solution(node)

  If (node.type = terminal)
    return(list(node.terminal-object))
  Else If (node.type = OR)
    return(get-node-solution(node.best-child))
  Else If (node.type = AND)
    Let solution = {}
    For child in node.children
      solution = append(solution, get-node-solution(child))
    return(solution)

compute-inner-values(sort-nodes(root-node), node-value-function)
return(get-node-solution(root-node))

```

FINDING MINIMUM VALUE

Another procedure 304b finds, for each node, the best (i.e., minimum) value of some value-function over all the set of pricing solutions involving that node. Price function 306a finds for
5 each itinerary, the cheapest price of any pricing solution that contains that itinerary. These values can be computed efficiently, if the value-function can be decomposed into a node-value-function.

Sub 23
10 ~~The best price value function 306a computes inner values, as above, and computes for every node, an outer-value, equal to the minimum value contributed by all parts of the graph except that represented by the node. For each node, the minimum value of the value-function over all solutions that involve the node, (i.e., the total-value) is computed as the sum of that node's inner-value and outer value.~~

15 The outer-value and total-value of a node are computed in a manner very similar to the computation of the inner-value. In particular, the outer-value for each node is calculated starting from the root of the graph, that has an outer-value of 0. Each
20 node propagates outer-values down to its children. An OR-node passes its outer-value unchanged. An AND-node adds to its outer-value the inner-values of all children except that being propagated to. At every node, after the outer-value has been computed, the total-value is computed as the sum of the inner-value and outer-value.
25

When outer-values are propagated from a node to its children, a minimum computation is performed. This is because each child may have more than one parent, and its outer-value must be the minimum outer-value contributed by any parent. See
30 TABLE 16 below.

TABLE 16

```

compute-outer-and-total-values(root-node, node-value-function)
    // Sort nodes and computer inner-values.
    Let sorted-nodes = sort-nodes(root-node)
    compute-inner-values(sorted-nodes, node-value-function)

    Let reversed-nodes = reverse(sorted-nodes)

// Initialize all nodes to have outer-values of infinity.
For node in reversed-nodes
    node.outer-value = infinity

// The root-node has an outer-value of 0.
first(reversed-nodes).outer-value = 0

For node in reversed-nodes

    // Compute the total-value for the node.
    node.total-value = node.inner-value + node.outer-value

    If (node.type = OR)
        // For OR nodes, the outer-value is propagated down to its children unchanged.
        For child in node.children
            child.outer-value = minimum(child.outer-value, node.outer-value)
    Else If (node.type = AND)
        // For AND nodes, the outer-value is propagated down by adding the inner-values of
        // all but the child being propagated to. This is equal to the node=s inner-value minus
        // the child=s inner-value, which is equal to the node=s total-value minus the child=s
        // inner-value.
        For child in node.children
            child.outer-value = minimum(child.outer-value, node.total-value - child.inner-value)

```

INVALIDATING NODES

~~It may be desirable to "invalidate" 304e certain nodes from the pricing-graph 38'. For example, itineraries containing or not containing specified airlines could be marked as not participating in the above algorithms, enabling the algorithms to find the best solutions involving or not involving these itineraries. The above algorithms can be easily adapted to accommodate checking whether the node is valid. In particular, the computation of inner-values, the first step in all the above~~

algorithms, is modified to mark for every node whether the node
 represents any valid partial pricing-solutions given a specific
 query parameter. This information can be used in the rest of the
 algorithms. Every terminal node contains a field "valid?" that
 is either true or false. The compute-inner-values procedure uses
 these values to set the "valid?" field for non-terminals. See
 TABLE 17 below.

TABLE 17

```

// Initialize all nodes to have outer-values of infinity.
For node in reversed-nodes
  node.outer-value = infinity

// The root-node has an outer-value of 0.
first(reversed-nodes).outer-value = 0

For node in reversed-nodes
  If (node.valid? = true)

    // Compute the total-value for the node.
    node.total-value = node.inner-value + node.outer-value

    If (node.type = OR)
      // For OR nodes, the outer-value is propagated down to its children unchanged.
      For child in node.children
        child.outer-value = minimum(child.outer-value, node.outer-value)
    Else If (node.type = AND)
      // For AND nodes, the outer-value is propagated down by adding the inner-values of
      // all but the child being propagated to. This is equal to the node=s inner-value minus
      // the child=s inner-value, which is equal to the node=s total-value minus the child=s
      // inner-value.
      For child in node.children
        child.outer-value = minimum(child.outer-value,
                                     node.total-value - child.inner-value)
  
```

```

sort-nodes (node)
If (not(find(node,nodes)))
For child in node.children
sort-nodes-inner(child)
nodes +=node
sort-nodes-inner(node);
return (nodes)
compute-inner-values(sorted-nodes, node-value-function)

```

```

For node in sorted-nodes
  If (node.type = terminal)
    node.inner-value = apply(node-value-function, node.terminal-object)
  Else If (node.type = OR)
    node.inner-value = infinity
    node.valid? = false
    For child in node.children
      If (child.valid? = true and child.inner-value < node.inner-value)
        node.inner-value = child.inner-value
        node.best-child = child
        node.valid? = true
  Else If (node.type = AND)
    node.inner-value = 0
    node.valid? = true
    For child in node.children
      If (child.valid? = true)
        node.inner-value += child.inner-value
  Else
    node.valid? = false

```

```

find-optimal-solution(root-node, node-value-function)

```

```

Subroutine get-node-solution(node)

  If (node.type = terminal)
    return(list(node.terminal-object))
  Else If (node.type = OR)
    return(get-node-solution(node.best-child))
  Else If (node.type = AND)
    Let solution = {}
    For child in node.children
      solution = append(solution, get-node-solution(child))
    return(solution)

```

```

compute-inner-values(sort-nodes(root-node), node-value-function)
If (root-node.valid? = true)
  return(get-node-solution(root-node))
Else
  return(nil)

```

```

compute-outer-and-total-values(root-node, node-value-function)

```

```

// Sort nodes and computer inner-values.
Let sorted-nodes = sort-nodes(root-node)
compute-inner-values(sorted-nodes, node-value-function)

Let reversed-nodes = reverse(sorted-nodes)

```

```

// Initialize all nodes to have outer-values of infinity.
For node in reversed-nodes
    node.outer-value = infinity

// The root-node has an outer-value of 0.
first(reversed-nodes).outer-value = 0

For node in reversed-nodes
    If (node.valid? = true)

        // Compute the total-value for the node.
        node.total-value = node.inner-value + node.outer-value

        If (node.type = OR)
            // For OR nodes, the outer-value is propagated down to its children unchanged.
            For child in node.children
                child.outer-value = minimum(child.outer-value, node.outer-value)
        Else If (node.type = AND)
            // For AND nodes, the outer-value is propagated down by adding the inner-values of
            // all but the child being propagated to. This is equal to the node=s inner-value minus
            // the child=s inner-value, which is equal to the node=s total-value minus the child=s
            // inner-value.
            For child in node.children
                child.outer-value = minimum(child.outer-value,
                                            node.total-value - child.inner-value)

```

ENUMERATING PRICING SOLUTIONS

It is often desirable to arbitrarily enumerate many pricing solutions: the best, the second-best, the third-best, etc.

The enumeration algorithm 304c maintains a queue of partial-solutions, ordered by the lowest possible total value of the value-function over all complete solutions that contain the partial-solution. At the start of the search, a single partial solution is constructed from the root node of the pricing-graph 38'. At each step the best partial-solution is dequeued, and expanded. Each partial-solution has a set of non-terminal nodes and a set of terminal objects. A partial-solution is expanded by selecting a non-terminal node and substituting the node's children (all of its children in the case of an AND, one of its children in the case of an OR). If a dequeued partial-solution contains only terminal objects, it is complete, and is returned. This process continues until the desired number of pricing-

solutions that can be specified by a user has been produced.

The algorithm can accommodate value-functions that cannot be decomposed into the sum of a node-value-function. It does this by applying a second penalty-value-function to partial pricing-solutions as it constructs them. This function returns a non-negative number when given a new terminal object and existing set of terminal objects. The number is added to the values produced by the normal node-value-function. If the number is positive, it acts as a penalty. An example of how this could be used is for the case where a penalty is applied if travel in two slices is on different airlines. The penalty-value-function would return a (positive) penalty if the terminal was an itinerary, and the set of existing terminals contained an itinerary with travel on different airlines. Otherwise it would return 0. See TABLE 18 below.

TABLE 18

```
compute-inner-values(sorted-nodes, node-value-function)
  For node in sorted-nodes
    If (node.type = terminal)
      node.inner-value = apply(node-value-function, node.terminal-object)
    Else If (node.type = OR)
      node.inner-value = infinity
      node.valid? = false
      For child in node.children
        If (child.valid? = true and child.inner-value < node.inner-value)
          node.inner-value = child.inner-value
          node.best-child = child
          node.valid? = true
```

```

Else If (node.type = AND)
  node.inner-value = 0
  node.valid? = true
  For child in node.children
    If (child.valid? = true)
      node.inner-value += child.inner-value
  Else
    node.valid? = false

```

```

find-optimal-solution(root-node, node-value-function)

```

```

Subroutine get-node-solution(node)

```

```

  If (node.type = terminal)
    return(list(node.terminal-object))
  Else If (node.type = OR)
    return(get-node-solution(node.best-daughter))
  Else If (node.type = AND)
    Let solution = {}
    For child in node.children
      solution = append(solution, get-node-solution(child))
    return(solution)

```

```

compute-inner-values(sort-nodes(root-node), node-value-function)

```

```

  If (root-node.valid? = true)
    return(get-node-solution(root-node))
  Else
    return(nil)

```

```

compute-outer-and-total-values(root-node, node-value-function)

```

```

  // Sort nodes and compute inner-values.
  Let sorted-nodes = sort-nodes(root-node)
  compute-inner-values(sorted-nodes, node-value-function)

```

```

  Let reversed-nodes = reverse(sorted-nodes)

```

```

  // Initialize all nodes to have outer-values of infinity.
  For node in reversed-nodes
    node.outer-value = infinity

```

```

  // The root-node has an outer-value of 0.
  first(reversed-nodes).outer-value = 0

```

```

  For node in reversed-nodes
    If (node.valid? = true)

```

```

// Compute the total-value for the node.
node.total-value = node.inner-value + node.outer-value

If (node.type = OR)
    // For OR nodes, the outer-value is propagated down to its children unchanged.
    For child in node.children
        child.outer-value = minimum(child.outer-value, node.outer-value)
Else If (node.type = AND)
    // For AND nodes, the outer-value is propagated down by adding the inner-values of
    // all but the child being propagated to. This is equal to the node=s inner-value minus
    // the child=s inner-value, which is equal to the node=s total-value minus the child=s
    // inner-value.
    For child in node.children
        child.outer-value = minimum(child.outer-value,
                                    node.total-value - child.inner-value)

```

Referring to FIG. 8, a diversity process 350 for selecting a diverse set of travel options from a larger set of candidate travel options is shown. The diversity process includes generating 352 an ordered list of travel requirements that represent conditions possibly required for a travel option to be the best travel option to generate. The diversity process 350 selects 354 for each travel requirement the one or more travel options that satisfy the requirement preferably by choosing those travel options that best satisfy one or more travel preference functions that can be used to order travel options.

For example, the air travel planning system generates the following 10 travel requirements for a set of travel options that each include one or more flights.

1. <none>
2. all flights on American Airlines.
3. all flights on United Airlines.
4. non-stop.
5. departing in morning.
6. departing in evening.

7. non-stop on American Airlines.
8. non-stop on United Airlines.
9. non-stop in morning.
10. non-stop in evening.

5 The diversity process 350 for each of the requirements the
planning system selects 354 from the large set of candidate
travel options e.g., the cheapest travel option that satisfies
the requirement. The cheapest option is generated; the cheapest
options all on American Airlines; the cheapest travel options all
10 on United Airlines; the cheapest travel options that are
non-stop; and so forth. These travel options are displayed 356
to provide a traveller a desirable option even if the traveller
has restrictions on the times the traveller can travel, or
preferences for one airline over another. These options are
15 possible more desirable than if the system had merely generated
and sent the 10 cheapest solutions without regard to producing a
diverse set of solutions taking into consideration preferences of
the traveller.

20 Referring to FIG. 9, an example 360 of a diversity process
350 is shown. The diversity process 360 generates a diverse list
of travel options from a larger set of travel options. The
diversity process iterates through a set of travel requirements
and selects the best travel option for each requirement. The
diversity process 360 can include an optional process that may
25 improve efficiency in some cases by eliminating more-restrictive
travel requirements that are satisfied by solutions selected for
less-restrictive travel requirements.

30 For example, given the ordered travel requirements in the
list above, if the cheapest travel option selected for the travel
requirement "all flights on American Airlines" happens to be a
non-stop option, then the travel requirement "non-stop on

American Airlines" is removed from the list of travel requirements to be satisfied, since the same travel option selected for the first requirement will be the best for the second more-specific requirement. This is only applied if the all restrictions in the first requirement are also found in the second requirement.

10 ~~The diversity process 360 thus includes a procedure for generating a diverse list of (N) travel options (Rts) from a larger list of travel options (Ts), that are the best travel options for a set of travel requirements (R), as defined by an ordering function F. The diversity process 360 generates 362 an prioritized (ordered) list of requirements Rs, and sorts 364 the list of travel options (Ts) by function (F) to produce a best-first ordered list (Ts2). The diversity process 360, initializes the list of result travel options (RTs) to be empty. If the remaining list of requirements (Rs) is empty, the process 360 returns an ordered list of diverse travel options (Rts). Otherwise, the diversity process selects 366 the first travel requirement (R) from the ordered list of requirements (Rs) and removes 368 a requirement (R) from the requirement list (Rs). The diversity process 360 find 370 a first (e.g., best) option T in the best-first ordered list (Ts2) that satisfies travel requirement (R).~~

25 ~~If the set of travel options is represented by a data structure that stores a large set of travel options by representing permitted combinations of smaller travel option components such as airline flights and fares. In such cases the travel option selection process above is implemented using a more complicated operation than searching through an ordered list. With the pricing-graph the process for finding 370 the best travel option that satisfies a travel requirement is implemented for a representation that expresses travel options in terms of,~~

A24
Cont'd

~~permitted combinations of smaller travel option components by disabling option components inconsistent with the requirement.~~

As shown in FIG. 9A, the process 360 can use the node invalidating functions to invalidate nodes 422 in the pricing graph 38 that are inconsistent with the requirements. The process 360 applies 424 an enumeration algorithm that extracts the best solution from the pricing graph representation. The diversity process 360 calls an enumeration function, as described above, to enumerate all of the valid pricing solutions from the pricing graph that are remaining after the diversity process selectively invalidated nodes in the graph inconsistent with the travel requirements.

Sub A27

If no option in the best-first ordered list (Ts2) satisfies 72 the requirement (R), the process 360 goes to check 374 if the remaining list of requirements (Rs) is empty. Otherwise, the diversity process determines 376 if a travel option T is not already in result travel options list (Rts). If the option T is not in the list (Rts), the diversity process adds 378 the travel option T to end of the result travel option list (Rts). If the size of the travel option list (RTs) is equal to or greater than N 380 the process returns the ordered list of diverse travel options.

Sub A28

Referring to FIG. 10A, the diversity process 360 could optionally determine 382 for a travel requirement (R2) in the set of travel requirements (Rs), whether the requirement (R2) is included in a prior requirement (R), and whether the travel option T also satisfies 384 the requirement (R2). If the travel option T satisfies the requirement (R2), the process 360 can remove 386 the requirement R2 from the requirement list (Rs) and return to determine 74 (FIG. 3) if the remaining list of requirements is empty.

Sub A29

Referring to FIG. 11, the process 362 to generate a

prioritized list of travel requirements is shown. The list may be a fixed list, for example the list of ten requirements in the example above. Alternatively, the list may be generated taking into account the number of solutions required, the ordering function, and the large set of candidate travel options. For example, the list may be generated 362 by filling 392 in a set of template requirements. A sample set of templates for air travel is

1. no requirement.
2. all flights on <airline>
3. non-stop.
4. outbound departure in <morning or afternoon or evening>.
5. return departure in <morning or afternoon or evening>.
6. outbound departure date <date>.
7. return departure date <date>.
8. non-stop on <airline>.
9. outbound departure date <date1> and return departure date <date2>.

~~The large candidate set of travel options may be analyzed 394 to find all parameters e.g., airlines found in any travel option, all departure dates for outbound and return, and all departure parts-of-day (morning, afternoon, evening) for outbound and return. The ordered list of requirements is generated by filling 96 in for each template all airlines, dates and parts-of-day present in the options.~~

The diversity process 360 can be run more than once with different travel option preference functions (a set of F's). For example, a travel planning system may output a diversity of travel options that include diverse options that are cheap and diverse options that are convenient, reflecting uncertainty in whether a traveller is cost-sensitive or convenience-sensitive.

Referring to FIG. 12, an alternative diversity process 100 to generate a diverse set of travel options from a larger set of travel options is shown. The alternative diversity process 400 generates the best one or more travel options as defined by each of a set of different travel preference functions. The alternative diversity process 400 defines a set of travel preference functions with each function capable to order travel options. In one example, the set might include "cheapest", "quickest", and "most-convenient" where each is a function that assigns a numerical score to a complete travel option (such as price, total-trip-time, and total trip-time with penalties for stops). Functions that assign numerical values based on combinations of cost and convenience are possible, such as ~~functions that weigh both price and time.~~

~~Given set of travel options Ts 401, a set of preference functions Fs, and a desired number of answers for each preference function Ns, the alternative diversity process 400 returns a reduced set of diverse travel options Rts. The alternative diversity process initializes 402 a list of result travel options RTs to be empty and for each preference function F in the set of preference functions Fs and number of travel options (N) in the set of desired number of answers in each preference function (Ns), the alternative diversity process 400 computes 404 the N best travel options in Ts as defined by F. For each travel option T, unless the travel option T is in the set of diverse travel options Rts 406, the alternative diversity process 400 adds 408 the travel option T to the set of diverse travel options Rts checks 410 the number of options. The alternative diversity process 400 outputs 412 the diverse set of travel options (RTs).~~

~~The diversity process can be run more than once with different travel option preference functions (a set of F's). For example, a travel planning system may wish to output a diversity~~

#33
Cont'd

~~of travel options that include diverse options that are cheap and~~
~~deverse options that are convenient, reflecting uncertainty in~~
~~whether a traveller is cost sensitive or convenience sensitive.~~

5 A computer travel planning system that outputs a
diversity of travel options may be built by combining a travel
planning system that transmits a larger set of solutions to a
second computer system that reduces the set of travel options
using diversity procedures as described above.

Other Embodiments

10 It is to be understood that while the invention has been
described in conjunction with the detailed description thereof,
the foregoing description is intended to illustrate and not limit
the scope of the invention, which is defined by the scope of the
appended claims. Other aspects, advantages, and modifications
are within the scope of the following claims.

What is claimed is: